

REMARKS

This substitute amendment has been filed to place the application in better form for examination. An action on the merits is respectfully requested. Please enter this response in lieu of the response submitted on November 5, 2007 for the above-identified application.

The Applicants have studied the Office Action dated August 3, 2007. Claims 2-14 remain pending. In the Office Action the Examiner:

- Objected to the disclosure for two informalities;
- Objected to claim 3, because of an informality;
- Objected to claims 2-14 under 35 U.S.C. 112, ¶ 2, second paragraph as being indefinite as to terminology used in the specification; and
- Indicated the allowable subject matter of claims 2-14.

Telephonic Interview

As an initial matter, the Applicants would like to thank Examiner Talbot for the telephonic interview held on November 15, 2007. The Applicant's representative Jon Gibbons participated in the telephone call. The Applicant's representative discussed the clarifying description for Figures 7, 8 and 17, along with changes to claim 1 to correspond to the figures. Examiner Talbot agreed to consider a substitute amendment to further clarify the invention.

Allowable Subject Matter

The Applicants also wish to thank Examiner Talbot for indicating the allowable subject matter of claims 2-14. The Applicants respectfully submit that this amendment places the application in a condition for allowance which allowance is respectfully requested.

Objection to Specification for Informalities

As noted above, the Examiner objected to the specification for two informalities. Specifically, the Applicants have amended the specification at paragraph [0048] and [0059] to remove the extraneous periods “.”. No new matter has been added. With this amendment the Applicants respectfully submits that the Examiner’s rejection to the specification has been overcome and should be withdrawn.

Objection to Claim 3 for an Informality

As noted above, the Examiner objected to claim 3 for an informality. The Applicants have carefully amended claim 3 to correct the typo of “from” to –form--. The Applicants respectfully submit that the Examiner’s objection to claim 3 has been overcome and respectfully request the Examiner’s objection be withdrawn.

35 U.S.C. 112, ¶ 2

As noted above, the Examiner rejected claims 1-14 under 35 U.S.C. 112, ¶ 2, as being indefinite. Per the Examiner's suggestion, the Applicants have carefully amended the specification to provide consistent use of terminology in the allowable claims. Specifically, the Applicants have amended the specification to recite consistent terminology as used in the allowable claims:

“top ply”

“bottom ply”

“first side of top ply”

“second side of top ply (i.e. inner side of top ply)”

“first side of bottom ply (i.e. inner side of bottom ply)”

“second side of bottom ply (i.e. backside of bottom ply)”

No new matter has been added. The Applicants respectfully submit that the Examiner's rejection to claims 2-14 has been overcome and the Examiner's rejections should be withdrawn.

CONCLUSION

The prior art made of record and not relied upon was reviewed and Applicants believe that such prior art is not pertinent to Applicants' disclosure.

No amendment made was related to the statutory requirements of patentability unless expressly stated herein. No amendment made was for the purpose of narrowing the scope of any claim, unless Applicants have argued herein that such amendment was made to distinguish over a particular reference or combination of references.

Applicants acknowledge the continuing duty of candor and good faith to disclose information known to be material to the examination of this application. In accordance with 37 CFR

§1.56, all such information is dutifully made of record. The foreseeable equivalents of any territory surrendered by amendment are limited to the territory taught by the information of record. No other territory afforded by the doctrine of equivalents is knowingly surrendered and everything else is unforeseeable at the time of this amendment by the Applicants and their attorneys.

The Commissioner is hereby authorized to charge any fees that may be required or credit any overpayment to Deposit Account 50-1556.

In view of the preceding discussion, it is submitted that the claims are in condition for allowance. Reconsideration and re-examination is requested.

PLEASE CALL the undersigned if the Examiner believes that there are any informalities that can be corrected by Examiner's amendment, or that in any way it would help expedite the prosecution of the patent application.

Respectfully submitted.

Date: November 15, 2007

By: /Jon A. Gibbons/
Jon A. Gibbons
(Reg. No.37,333)
Attorney for Applicant

FLEIT KAIN GIBBONS
GUTMAN BONGINI & BIANCO P.L.
One Boca Commerce Center
551 N.W. 77th Street
Suite 111, Boca Raton, Florida 33487
Telephone: (561) 989-9811
Facsimile: (561) 989-9812
www.FocusOnIP.com

EXPRESS MAIL LABEL NO. EV343427046US

DATE MAILED: December 18, 2003

PATENT

INVENTORS: **Warren M. FABEL**
 Jose B. CORTEZ
 Glen A. AUCHTER

MULTI-LABEL MAILING FORM INCLUDING CERTIFIED SELF-MAILER

PARTIAL WAIVER OF COPYRIGHT

[0001] All of the material in this patent application is subject to copyright protection under the copyright laws of the United States and of other countries. As of the first effective filing date of the present application, this material is protected as unpublished material. However, permission to copy this material is hereby granted to the extent that the copyright owner has no objection to the facsimile reproduction by anyone of the patent documentation or patent disclosure, as it appears in the United States Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

CROSS-REFERENCED APPLICATIONS

[0002] This non-provisional application is a continuation-in-part of the non-provisional patent application serial number 10/378,163 with inventor Warren Fabel entitled "MULTI-LABEL MAILING FORM FOR NON-IMPACT PRINTER" filed February 28, 2003, which is hereby incorporated by reference in its entirety. This non-provisional application is also a continuation-in-part of the non-provisional patent application serial number 10/255,375 with inventor Warren Fabel entitled "SINGLE SIDE IMAGED POSTAL FORM ASSEMBLY" filed September 26, 2002, which is hereby incorporated by reference in its entirety. Both of the aforementioned non-provisional applications are

EXPRESS MAIL LABEL NO. EV343427046US

continuation-in-part applications of the non-provisional patent application serial number 09/293,496 with inventor Fabel entitled "SINGLE-SIDE IMAGED POSTAL FORM ASSEMBLY" filed April 15, 1999, which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTIONField of the Invention

[0003] This invention generally relates to the field of mailing forms and more specifically to mailing forms that can be folded to include a document firmly situated inside the mailing form when in folder configuration.

Description of Related Art

[0004] As technology progresses, the business office is becoming more and more automated. Faxes, file servers, email, teleconferencing and cell phones have revolutionized the way firms do business. Self-mailing documents, in particular, have enjoyed increasing popularity. A self-mailer is a consumable paper product that allows for quick and easy printing and mailing of information. A self-mailer can include an envelope, an insert and a return envelope, which may be created by folding the original document. For example, self-mailers are used to send account statements, invoices, checks, to customers and employees of a business. The commonly owned U.S. Patent Applications described above provide more information on self-mailers. A self-mailer allows a firm or business to print directly onto one product all of the information necessary for mailing to a customer, client or employee. This is advantageous as it eliminates the separate printing of an envelope, an insert and a return envelope, as well as the need for the insertion of the return envelope and the

EXPRESS MAIL LABEL NO. EV343427046US

insert into the envelope. Self-mailers, however, do not come without their drawbacks.

[0005] One problem is producing the self-mailer. Self-mailers often require folding and sealing before sending out. Current folding/sealing machines are bulky and costly. Thus, businesses are forced to buy additional equipment, apart from software and printers, in order to produce a self-mailer. This is cost prohibitive for many businesses. Therefore, a need exists to provide a cost effective method of producing self-mailers for small and medium businesses.

[0006] Another problem with the production of self-mailers is that current business form printing software requires duplex or multiple pass printers. This is disadvantageous, as the current installed base of printers substantially comprises simplex or single pass printers. It would be advantageous for business form printing software to support the current installed base of single pass printers (simplex), as it is cost effective for those recipients to continue using their current printers, as opposed to purchasing new printers. Therefore, a need exists for a business form printing system that supports simplex or single pass printers.

[0007] Non-impact printers, such as laser or ink jet printers, are being increasingly used to provide a fast, economical, and convenient method of printing data on various media, including self-mailers. Multi-part forms, including envelopes in which documents are sent, together with the documents themselves, have been manufactured for use in impact printers. Such forms are typically assembled into webs with sprocket holes extending along one or both lateral edges to facilitate handling through a pin feed impact printer. Transferable coatings are selectively placed on one or more of the sheets making up the assembly, so that impact-printing forces are transferred to produce characters on intermediate document surfaces. This approach has further been modified to provide a remittance envelope, in which various

EXPRESS MAIL LABEL NO. EV343427046US

materials, such as a check and a portion of the statement, may be returned to the organization sending the statement.

[0008] However, with the increasing popularity of non-impact printers, especially among small business organizations, the percentage of organizations having the impact printers necessary to use such multi-part forms is decreasing.

Therefore, what is needed is a self-mailer configured for use with non-impact printers. However, by simply adapting the standard available technologies to produce forms that can be used with non-impact printers results in forms that do not have flexibility and the capability for efficient use with non-impact printers.

For example, impact self-mailers produced by machine-fold and seal technologies available in the 1980s and 1990s were often burdensome or clumsy to open. A perforated strip had to be removed from at least three, and sometimes four, sides of the mail piece. At least two of these strips ran at right angles to the paper grain whereby perforations are least effective for providing a clean tear.

[0009] Furthermore, previously available self-mailers often must be processed through automatic folding/sealing machines to be used in a practical manner. Such automatic folding machines are examples of equipment not available to many small business organizations.

[0010] Currently, there is no efficient solution to handle information where a notice, announcement or other information typically printed on an information postcard is sent via Certified Mail. Information postcards are used in many situations to satisfy notice requirements under local, state and federal laws. These notice requirements vary from eviction notices and parking violations, to satisfying a lien against equipment and/or belongings. In this example, the sender of the information document must match up the document to the requirements of Certified Mail. This is time consuming and prone to errors. Specifically, a user must manually fill out the "Certified Mail Postcard" (United

EXPRESS MAIL LABEL NO. EV343427046US

States Postal Service Form 3811 and often referred to as Registered Mail in non-U.S. Countries) and the "Receipt for Certified Mail" (United States Postal Service Form 3800) are manually filled out or printed separately from the information post card.

[0011] Therefore, a need exists to overcome the problems with the prior art as discussed above.

SUMMARY OF THE INVENTION

[0012] Briefly, in accordance with the present invention, disclosed is a mailing form for facilitating the mailing of an information post card or information document combined with "Certified Mail Postcard" (United States Postal Service Form 3811 and often referred to as Registered Mail in non-U.S. Countries) and the "Receipt for Certified Mail" (United States Postal Service Form 3800). In an embodiment of the present invention, the mailing form includes a bottom ply of the mailing form and an adhesive interspersed between the ~~front face of the first~~ side of the bottom ply (i.e. the inner side of the bottom ply) and the ~~backside second side of the top ply (i.e. the inner side of the top ply)~~. The mailing form further includes a top ply of the mailing form located on top of the bottom ply and a removable portion of the top ply extending over the first side of the top ply, such that removal of the removable portion exposes the adhesive. The mailing form further includes document information printed on the ~~back face~~ second side of the bottom ply. The mailing form further includes a vertical fold line for folding the mailing form after the top ply has been removed, the adhesive securing the mailing form when folded along the vertical fold line and a horizontal strip of the ~~front face first side~~ of the bottom ply (i.e. the inner side of the bottom ply) ~~located on the first side of the bottom ply~~, the horizontal strip including adhesive that is exposed after the mailing form is folded along the vertical fold line. The mailing form further includes a horizontal fold line for

EXPRESS MAIL LABEL NO. EV343427046US

folding the mailing form that has been folded along the vertical fold line, the adhesive of the horizontal strip securing the mailing form when folded along the horizontal fold line. When the mailing form is in folder configuration, the document information is firmly situated within the mailing form as required by the United States Postal Service (USPS).

[0013] In an embodiment of the present invention, the mailing form further includes a first perforation along the top margin of the top ply and the bottom ply and a second perforation along the bottom margin of the top ply and the bottom ply. The first perforation and the second perforation can be torn when the mailing form is in folder configuration, such that the mailing form can be unfolded along the horizontal fold line.

[0014] In an embodiment of the present invention, a method for facilitating the mailing of a document is further disclosed. The method includes providing a mailing form comprising a bottom ply, a top ply located on top of the bottom ply, and an adhesive interspersed between the ~~front face of the first side of the bottom ply~~ (i.e. the inner side of the bottom ply) and the ~~backside~~ second side of the top ply (i.e. inner side of the top ply). The method further includes printing document information on the ~~back face~~ second side of the bottom ply and removing a removable portion of the top ply extending over the first side of the top ply, such that removal of the removable portion exposes the adhesive. The method further includes folding the mailing form along a vertical fold line after the top ply has been removed, the adhesive securing the mailing form when folded along the vertical fold line. A horizontal strip of the ~~front face of the bottom ply located on the first side of the bottom ply~~ (i.e. the inner side of the bottom ply) is exposed after the mailing form is folded along the vertical fold line, the horizontal strip including adhesive. The method further includes folding the mailing form along a horizontal fold line, the adhesive of the horizontal strip securing the mailing form when folded along the horizontal fold line. When the

EXPRESS MAIL LABEL NO. EV343427046US

mailing form is in folder configuration, the document information is firmly situated within the mailing form.

[0015] In an embodiment of the present invention, the method further includes tearing a first perforation running along the top margin of the top ply and the bottom ply and a second perforation running along the bottom margin of the top ply and the bottom ply when the mailing form is in folder configuration, such that the mailing from can be unfolded along the horizontal fold line.

[0016] The features of the present invention are advantageous as all printed information is printed on one face of the self-mailer and thus it allows the self-mailer to be printed in a typical sheet-fed non-impact printer. Additionally, it allows the postage indicia and Facing Identification Mark to be printed within 1/8 of an inch of the top edge of an envelope, as required by the U.S. Postal Service (USPS). Further, it allows all of the text printed on the self-mailer to be printed in the same orientation. This simplifies the printing process and provides for an efficient allocation of resources.

[0017] Another advantage of the present invention is that a self-mailer, including a document such as a certified mail form, is provided with an attached "Receipt for Certified Mail" (United States Postal Service Form 3800). This embodiment of the present invention allows for the printing of the inserted document and the receipt at the same time and in one printer pass. This results in a quick and easy generation of the self-mailer and associated receipt.

[0018] Another advantage of the present invention is that the present invention eliminates the possibility of a mismatch between a document and a Certified Mail card. Since both items are printed onto the same self-mailer, there is no need to seek matching documents and collate them together. Instead, both items are printed onto the same self-mailer and folded and sealed together to produce an item that is mailed.

EXPRESS MAIL LABEL NO. EV343427046US

[0019] Another advantage of the present invention is that the self-mailer is easily printable by a standard non-impact printer. Printing of the self-mailer does not require the adjustment of the printer. This is beneficial to the consumer as it results in a more efficient printing process.

[0020] The foregoing and other features and advantages of the present invention will be apparent from the following more particular description of the preferred embodiments of the invention, as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The subject matter, which is regarded as the invention, is particularly pointed out and distinctly claimed in the claims at the conclusion of the specification. The foregoing and other features and also the advantages of the invention will be apparent from the following detailed description taken in conjunction with the accompanying drawings. Additionally, the left-most digit of a reference number identifies the drawing in which the reference number first appears.

[0022] FIG. 1 shows the ~~front-side~~first side of a ~~first-ply~~top ply of the mailing form in one embodiment of the present invention.

[0023] FIG. 2 shows the ~~front-side~~first side of a ~~second-ply~~bottom ply (i.e. inner side of the bottom ply) of the mailing form in one embodiment of the present invention.

[0024] FIG. 3A shows the ~~backside~~second side of the bottom ply (i.e. backside of the bottom ply) of the mailing form in one embodiment of the present invention.

EXPRESS MAIL LABEL NO. EV343427046US

[0025] FIG. 3B shows a removable portion of the ~~second ply~~ bottom ply in one embodiment of the present invention.

[0026] FIG. 4 shows the ~~backside~~ remaining portion of the bottom ply of the mailing form after removal of the removable portion of the ~~second ply~~ bottom ply in one embodiment of the present invention.

[0027] FIG. 5A shows the ~~backside~~ second side of the bottom ply (i.e. backside of the bottom ply) of the mailing form during a first folding action in one embodiment of the present invention.

[0028] FIG. 5B shows the mailing form after the first folding action in one embodiment of the present invention.

[0029] FIG. 6A shows the mailing form during a second folding action in one embodiment of the present invention.

[0030] FIG. 6B shows the mailing form after the second folding action in one embodiment of the present invention.

[0031] FIG. 7 shows the ~~backside~~ first side of a ~~first ply~~ top ply of the mailing form in one embodiment of the present invention.

[0032] FIG. 8 shows the ~~second side~~ backside of a ~~second ply~~ bottom ply (i.e. the backside of the bottom ply) of the mailing form in one embodiment of the present invention.

[0033] FIG. 9 shows the ~~backside~~ second side of the bottom ply (i.e. the backside of the bottom ply) of the mailing form during removal of the removable portion of the ~~second ply~~ backside of the bottom ply in one embodiment of the present invention.

EXPRESS MAIL LABEL NO. EV343427046US

[0034] FIG. 10 shows the ~~backside~~remaining portion of the bottom ply of the mailing form after removal of the removable portion of the ~~second ply~~bottom ply in one embodiment of the present invention.

[0035] FIG. 11 shows the removable portion of the ~~second ply~~bottom ply in one embodiment of the present invention.

[0036] FIG. 12 shows the ~~backside~~second side of the bottom ply (i.e. backside of the bottom ply) of the mailing form during a first folding action in one embodiment of the present invention.

[0037] FIG. 13 shows the mailing form after the first folding action in one embodiment of the present invention.

[0038] FIG. 14 shows the mailing form during a second folding action in one embodiment of the present invention.

[0039] FIG. 15 shows the mailing form after the second folding action in one embodiment of the present invention.

[0040] FIG. 16 shows the mailing form during removal of a receipt in one embodiment of the present invention.

[0041] FIG. 17 shows another embodiment of the ~~backside~~first side of a first ~~ply~~top ply of the mailing form in one embodiment of the present invention.

[0042] FIG. 18 shows another embodiment of the ~~backside~~second side of a ~~bottom ply~~second ply (i.e. the backside of the bottom ply) of the mailing form in one embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

EXPRESS MAIL LABEL NO. EV343427046US

[0043] The present invention solves the problems with the prior art by providing a self-mailer that (a) provides a combination of a information post card or information document combined with "Certified Mail Postcard" (United States Postal Service Form 3811 and often referred to as Registered Mail in non-U.S. Countries) and the "Receipt for Certified Mail" (United States Postal Service Form 3800) and (b) can be simplex printed to include all addressing and electronic PC postage, including Information-Based Indicia (IBI) and FIM indicia and automatic positioning of same, in a single pass through the simplex printer.

First Embodiment

[0044] FIG. 1 shows the ~~front-side~~first side of a ~~top ply~~first-ply 102 of the mailing form, or self-mailer, in one embodiment of the present invention. FIG. 1 shows that the ~~first-ply~~top ply 102 is a rectangular sheet of paper having dimensions of a standard sheet of paper, e.g., 8.5x11 inches, 8.5x14 inches or A4. It is important to note, that other paper dimensions are possible to those skilled in the art, within the true scope and spirit of the present invention. The ~~first-ply~~top ply 102 is composed of any number of paper materials and composites that are used as paper substitutes. The ~~first-ply~~top ply 102 can receive printed information when passed through a simplex non-impact printer.

[0045] FIG. 1 shows that the ~~first-ply~~top ply 102 includes a vertical fold line 120 that evenly divides the ~~first-ply~~top ply 102 vertically in half. FIG. 1 also shows that the ~~first-ply~~top ply 102 includes a horizontal fold line 121 that also evenly divides the ~~first-ply~~top ply 102 in half, but horizontally. Thus, the ~~front-face~~first side of the ~~first-ply~~top ply 102 is divided into four quadrants by the vertical fold line 120 and the horizontal fold line 121. FIG. 1 further shows that the ~~first-ply~~top ply 102 includes a perforation 130 running along the top edge of the ~~first-ply~~top ply 102 and a perforation 131 running along the bottom edge of the ~~first-ply~~top ply 102.

[0046] FIG. 1 further shows that the ~~first-ply~~top ply 102 includes a die cut 141 that runs along the top edge of the ~~first-ply~~top ply 102 from vertical fold line 120 to the end of the ~~first-ply~~top ply 102. In addition, the ~~first-ply~~top ply 102 includes a die cut 140 that runs along the vertical fold line 120 from the top of the ~~first-ply~~top ply 102 to the die cut 141. A die cut is a continuous or substantially continuous cut of a ply or sheet of paper. A perforation is a periodic series of small cuts or holes in a ply or sheet of paper. Various well-known form

EXPRESS MAIL LABEL NO. EV343427046US

manufacturing processes can be used to form die cuts and perforations. In one embodiment, the fold lines 121 and 120 are perforations.

[0047] The fold lines, perforations and die cuts of the ~~first-plytop ply~~ 102 create various areas in the ~~front-face~~first side of the ~~first-plytop ply~~ 102. Area 110 is located in the top right quadrant of the ~~first-plytop ply~~ 102, bounded on the bottom by fold line 121, bounded on the left by fold line 120 and bounded on the top by perforation 130. Area 111 is located in the bottom right quadrant of the ~~first-plytop ply~~ 102, bounded on the bottom by perforation 131, bounded on the left by fold line 120 and bounded on the top by fold line 121. Area 112 is located in the bottom left quadrant of the ~~first-plytop ply~~ 102, bounded on the bottom by perforation 131, bounded on the right by fold line 120 and bounded on the top by fold line 121. Area 113 is located in the top left quadrant of the ~~first-plytop ply~~ 102, bounded on the bottom by fold line 121, bounded on the right by fold line 120 and bounded on the top by perforation 130. Horizontal strip 145 is located in the top right quadrant of the ~~first-plytop ply~~ 102, bounded on the bottom by die cut 141 and bounded on the left by die cut 140.

[0048] In one embodiment of the present invention, document information is printed on an informational postcard or information document can be printed in areas 110 and 111. The document information is information necessary to satisfy notice requirements under local, state and federal laws. These notice requirements vary from eviction notices and parking violations, to satisfying a lien against equipment and/or stored belongings. --In another embodiment of the present invention, variable information can be printed in areas 112 and 113. The variable information can include, among other things, a sender address, a recipient address, postage indicia and a Facing Identification Mark (FIM - a symbol on envelopes used for facilitating the sorting and routing of mail). Postage indicia include stamp postage, tape postage, PC postage and the like.

EXPRESS MAIL LABEL NO. EV343427046US

[0049] In an embodiment of the present invention, postage indicia and FIM are printed in area 112 or 113 near fold line 121. The U.S. Postal Service (USPS) requires that postage indicia and FIM be printed within 1/8 of an inch of the top edge of an envelope. Many simplex printers have a border of non-printable area, commonly 1/4" on all four sides. Typically, it is difficult, if not impossible, to program a sheet-fed printer to print data precisely near the top edge of paper, as the top edge is the first portion of the paper that is fed into the printer known as the gripper portion. If the postage indicia and FIM were located near the top of the ~~first-ply~~top ply 102 (such as above the perforation 130), it would be problematic to print the postage indicia and FIM within 1/8 of an inch of the top edge of the ~~first-ply~~top ply 102. Thus, the postage indicia and FIM are printed near the horizontal fold line 121, which is away from the edge of the sheet of the ~~first-ply~~top ply 102.

[0050] Typically, it is possible to program a sheet-fed printer to print data precisely in areas away from the edges of the paper.

[0051] Note that the document information printed in the areas 110 and 111 and the variable information printed in areas 112 and 113 can be printed in a downwards-facing or in an upwards facing orientation.

[0052] The foregoing features of the present invention are advantageous as all printed information is printed on the ~~front-face~~first side of the ~~first-ply~~top ply 102 and thus it allows the self-mailer to be printed in a typical sheet-fed non-impact printer. Additionally, it allows the postage indicia and FIM to be printed within 1/8 of an inch of the top edge of the mail piece, as required by the USPS.

[0053] FIG. 2 shows the ~~front-side~~first side of a ~~second-ply~~bottom ply (i.e. inner side of the bottom ply) 202 of the mailing form in one embodiment of the present invention. The ~~second-ply~~bottom ply 202 is of the same size and constitution as the ~~first-ply~~top ply 102. As shall be seen below, the ~~second-ply~~bottom ply 202 is

manufactured for superimposing below, and lining up with, the first-plytop ply 102.

[0054] FIG. 2 shows a die cut 240 running along the vertical midsection of the second-plybottom ply 202 and curving to the right to meet the right edge of the second-plybottom ply 202. In another embodiment, there are other geometric angles or combinations of angles and curves that are used, such as a right-angle. The horizontal portion of the die cut 240 is referred to as die cut 205. FIG. 2 also shows a fold line 221 running along the horizontal midsection of the second-plybottom ply 202, starting at the die cut 240 and extending to the right edge of the second-plybottom ply 202. FIG. 2 further shows a perforation 230 running along the top edge of the second-plybottom ply 202, starting at the die cut 240 and extending to the right edge of the second-plybottom ply 202. FIG. 2 further shows a perforation 231 running along the bottom edge of the second-plybottom ply 202, starting at the die cut 240 and extending to the right edge of the second-plybottom ply 202.

[0055] Die cut 240 bounds the area of the removable portion 203 of the second-plybottom ply 202. Because a die cut is a substantially continuous cut of the material that constitutes second-plybottom ply 202, die cut 240 effectively disconnects the removable portion 203 from the rest of the second-plybottom ply 202. The removable portion 203 and its functions are described in greater detail below.

[0056] When the first-plytop ply 102 is superimposed on top of second-plybottom ply 202, the perforation 230 is collinear, that is it lies parallel, with the perforation 130, the perforation 231 is collinear with the perforation 131, the fold line 221 is collinear with the fold line 121 and a substantial portion of the die cut 240 is collinear with the fold line 120. Furthermore, die cut 205 is collinear with die cut 141.

[0057] FIG. 3A shows the ~~backside~~second side of the bottom ply (i.e. ~~backside of the bottom ply~~) of the mailing form 300, or self-mailer, in one embodiment of the present invention. The mailing form 300 comprises the ~~first ply~~top ply 102 laid on top of the ~~second ply~~bottom ply 202 such that the ~~front face~~first side of the ~~second ply~~inner side of the bottom ply 202 meets the ~~back face~~second side of the ~~first ply~~top ply (i.e. ~~inner side of the top ply~~) 102. FIG. 3A shows the ~~back face~~second side of the ~~second ply~~bottom ply (i.e. ~~backside of the bottom ply~~) 202, as the ~~front face~~first side of the ~~second ply~~inner side of the bottom ply 202 is not visible due to the ~~first ply~~top ply 102 laying on top of the ~~front face~~first side of the ~~second ply~~bottom ply 202. FIG. 3A also shows the ~~back face~~second side of the ~~first ply~~top ply (i.e. ~~inner side of the top ply~~) 102, visible only as the ~~second ply~~bottom ply 202 is peeled off.

[0058] As explained above, the die cut 240 bounds the area of the removable portion 203 of the ~~second ply~~bottom ply 202. Die cut 240 effectively dis-adheres or peels-off the removable portion 203 from the rest of the ~~second ply~~bottom ply 202. FIG. 3A shows that the removable portion 203 of the ~~second ply~~bottom ply 202 can be removed by peeling the removable portion 203 from the self-mailer 300. The ~~front face~~first section of the removable portion 203 of the ~~second ply~~bottom ply 202 (i.e., that face of the removable portion 203 that contacts the ~~first ply~~top ply 102) is coated with a releasable substrate 305 such as silicon. Further, the area of the ~~back face~~second side of the ~~first ply~~top ply (i.e. ~~the inner side of the top ply~~) 102 that contacts the ~~front face~~first section of the removable portion 203 is coated with an adhesive 304.

[0059] Thus, the releasable substrate 305 on the ~~front face~~first section of the removable portion 203 of the ~~second ply~~bottom ply 202 contacts and releasably adheres to the adhesive 304 on the ~~back face~~second side of the ~~first ply~~top ply (i.e. ~~inner side of the top ply~~) 102. As the removable portion 203 of the ~~second ply~~bottom ply 202 is pulled off of the ~~first ply~~top ply 102, the releasable

substrate 305 on the ~~backside~~second side of the bottom ply (backside of the bottom ply) of the removable portion 203 releases from the adhesive 304 on the ~~back-face~~second side of the first plytop ply (i.e. inner side of the top ply) 102.

This allows the removable portion 203 to be removed easily when pulled such that the releasable substrate 305 on the ~~front-face~~first section of the removable portion 203 releases from the adhesive 304 on the ~~back-face~~second side of the first plytop ply (i.e. inner side of the top ply) 102. FIG. 3B shows the removable portion 203 of the ~~second ply~~bottom ply 202 in one embodiment of the present invention. FIG. 3B shows the removable portion 203 after: it has been removed from the self-mailer 300.

[0060] FIG. 4 shows the ~~backside~~second side of the bottom ply (i.e. backside of the bottom ply) of the mailing form 300 after removal of the removable portion 203 of the second side of the second ply bottom ply 202 (i.e. the backside of the bottom ply) in one embodiment of the present invention. FIG. 4 shows that after removal of the removable portion 203 of the second side of the second plybottom ply 202 (i.e. backside of the bottom ply), a portion of the ~~back-face~~second side of the first plytop ply (i.e. inner side of the top ply) 102, including the adhesive 304, is exposed. Note that a portion of the ~~second ply~~bottom ply 202 has not been removed and is still present.

[0061] FIG. 4 also shows that horizontal strip 145 of the first plytop ply 102 has been removed along with the removable portion 203 of the ~~second ply~~bottom ply 202. Horizontal strip 145 is located in the first plytop ply 102, bounded by die cut 141 and by die cut 140. When the first plytop ply 102 is placed on top of ~~second ply~~bottom ply 202, die cut 205 is collinear with die cut 141. The removable portion 203 of the ~~second ply~~bottom ply 202 is coupled with the horizontal strip 145 via adhesive or the like. When the removable portion 203 of the ~~second ply~~bottom ply 202 is removed, the horizontal strip 145, being

coupled to the removable portion 203 and being detached from the rest of the first-plytop ply 102, is removed along with the removable portion 203.

[0062] FIG. 5A shows the backsidesecond side of the bottom ply (i.e. backside of the bottom ply) of the mailing form 300 during a first folding action in one embodiment of the present invention. FIG. 5A shows the self-mailer 300 being folded for mailing. FIG. 5A shows that the self-mailer 300 is folded along vertical fold line 120 such that the back-facesecond side of the second ply of the left side of self-mailer 300 meets the back-facesecond side of the top ply of the rightfirst side of self-mailer 300. Upon folding, note that the rightfirst side of the back-facesecond side of the first-plytop ply 102 is lined with an adhesive 304. Thus, when the self-mailer 300 is folded along vertical fold line 120, the adhesive 304 contacts and adheres to corresponding areas in the opposing face. Namely, the adhesive 304 on the rightfirst side of the first-plytop ply 102 contacts and adheres to corresponding areas in the left side of the second plybottom ply 202.

[0063] The result of the folding action of FIG. 5A is shown in FIG. 5B. FIG. 5B shows the mailing form 300 after the first folding action in one embodiment of the present invention. FIG. 5B shows that after folding along the vertical fold line 120, the areas 110 and 111 are exposed. In one embodiment of the present invention, document information can be printed in areas 110 and 111. FIG. 5B also shows that a horizontal strip 502 including adhesive 304 is also exposed due to the removal of the horizontal strip 145, as described with reference to FIG. 4 above.

[0064] FIG. 6A shows the mailing form 300 during a second folding action in one embodiment of the present invention. FIG. 6A shows the self-mailer 300 being further folded for mailing. FIG. 6A shows that the self-mailer 300 is folded along horizontal fold line 121 such that the area 110 of self-mailer 300 meets the area 111 of self-mailer 300. Upon folding, note that the horizontal strip 502 is lined

EXPRESS MAIL LABEL NO. EV343427046US

with an adhesive 304. Thus, when the self-mailer 300 is folded along horizontal fold line 121, the adhesive 304 contacts and adheres to corresponding areas in the opposing face. Namely, the adhesive 304 on the horizontal strip 502 contacts and adheres to corresponding areas below the perforation 131 of the ~~first-plytop ply~~ 102.

[0065] The result of the folding action of FIG. 6A is shown in FIG. 6B. FIG. 6B shows the mailing form 300 after the second folding action in one embodiment of the present invention. FIG. 6B shows that after folding along the horizontal fold line 121, the area 113 of the ~~first-plytop ply~~ 102 is exposed. In one embodiment of the present invention, variable information, such as outgoing postal or mailing address or a receipt address, can be printed in area 113. FIG. 6B also shows that upon folding along the horizontal fold line 121, perforation 130 and 131 are collinear.

[0066] The foregoing features of the present invention are advantageous as they result in document information being firmly situated between layers of paper of the ~~first-plytop ply~~ 102 and the ~~second-plybottom ply~~ 202. Further, the document information is sealed along the edges by the adhesive 304. This produces a mailer that securely carries document information and is able to survive the rigors of mail processing by the USPS and other entities.

[0067] After mailing the completely folded mailing form 300 of FIG. 6B, the mailing form 300 can be opened by the postal carrier or mail carrier by tearing along the perforation 130. Note that upon folding along the horizontal fold line 121, perforation 130 and 131 are collinear. Also note that the adhesive 304 on the horizontal strip 502 contacts and adheres to corresponding areas below the perforation 131 of the ~~first-plytop ply~~ 102. Thus, upon tearing along perforations 130 and 131 and discarding the resultant strip, the adhesive on horizontal strip 502 is eliminated. The mailing form 300 can then be opened along the horizontal fold line 121, as shown in FIG. 6A, exposing areas 110 and 111.

Second Embodiment

[0068] FIG. 7 shows the ~~backside-first side~~ of a ~~first-plytop ply~~ 702 of the mailing form, or self-mailer, in a second embodiment of the present invention. FIG. 7 shows that the ~~first-plytop ply~~ 702 is a rectangular sheet of paper having dimensions of 8.5x14 inches, for example.

[0069] FIG. 7 shows that the ~~first-plytop ply~~ 702 includes a vertical fold line 720 running vertically along the ~~first-plytop ply~~ 702. FIG. 7 also shows that the ~~first-plytop ply~~ 702 includes a horizontal fold line 721 running horizontally along the ~~first-plytop ply~~ 702. FIG. 7 further shows that the ~~first-plytop ply~~ 702 includes a perforation 722 running vertically near the right edge of the ~~first-plytop ply~~ 702. Additionally, FIG. 7 shows that the ~~first-plytop ply~~ 702 includes a perforation 730 running along the top edge of the ~~first-plytop ply~~ 702 from the left edge of the ~~first-plytop ply~~ 702 to the perforation 722 and a perforation 731 running along the bottom edge of the ~~first-plytop ply~~ 702 from the left edge of the ~~first-plytop ply~~ 702 to the perforation 722.

[0070] FIG. 7 further shows that the ~~first-plytop ply~~ 702 includes a die cut 741 that runs along the top edge of the ~~first-plytop ply~~ 702 from vertical fold line 720 to the left edge of the ~~first-plytop ply~~ 702. In addition, the ~~first-plytop ply~~ 702 includes a die cut 740 that runs along the vertical fold line 720 from the top of the ~~first-plytop ply~~ 702 to the die cut 741. In one embodiment, the fold lines 721 and 720 are perforations.

[0071] The fold lines, perforations and die cuts of the ~~first-plytop ply~~ 702 create various areas in the ~~front-facefirst side~~ of the ~~first-plytop ply~~ 702. Area 710 is located in the upper portion of the ~~first-plytop ply~~ 702, bounded on the top by

EXPRESS MAIL LABEL NO. EV343427046US

perforation 730, bounded on the bottom by fold line 721, bounded on the left by fold line 720 and bounded on the right by perforation 722. Area 711 is located in the bottom portion of the ~~first plytop ply~~ 702, bounded on the bottom by perforation 731, bounded on the left by fold line 720, bounded on the top by fold line 721 and bounded on the right by perforation 722. Area 712 is located in the bottom portion of the ~~first plytop ply~~ 702, bounded on the bottom by perforation 731, bounded on the right by fold line 720 and bounded on the top by fold line 721. Area 713 is located in the top portion of the ~~first plytop ply~~ 702, bounded on the bottom by fold line 721, bounded on the right by fold line 720 and bounded on the top by perforation 730.

[0072] Area 714 is located in the upper portion of the ~~first plytop ply~~ 702, bounded on the bottom by fold line 721 and bounded on the left by perforation 722. Area 715 is located in the bottom portion of the ~~first plytop ply~~ 702, bounded on the left by perforation 722 and bounded on the top by fold line 721. Horizontal strip 745 is located in the top portion of the ~~first plytop ply~~ 702, bounded on the bottom by die cut 741 and bounded on the right by die cut 740.

[0073] In one embodiment of the present invention, document information can be printed in areas 710 and 711. In another embodiment of the present invention, variable information can be printed in areas 712 and 713. In yet another embodiment of the present invention, receipt information can be printed in areas 714 and 715. In this embodiment, the receipt is typically a copy of information that is included in the document information of areas 710 and 711. The receipt is retained by the sender of the mailing form 300 as a "Receipt for Certified Mail" (e.g. United States Postal Form 3800 or equivalent) after being "round stamped" by the receiving postal clerk of the United States Postal Service of the self-mailer that was mailed.

[0074] In yet another embodiment of the present invention, postage indicia and FIM are printed in area 712 or 713 near fold line 721, which is away from the

EXPRESS MAIL LABEL NO. EV343427046US

edge of the sheet of the ~~first plytop ply~~ 702. Note that the document information printed in the areas 710 and 711, the variable information printed in areas 712 and 713 and the receipt information printed in areas 714 and 715 can be printed in a downwards-facing or in an upwards facing orientation.

[0075] The foregoing features of the present invention are advantageous as all printed information is printed on the ~~front face~~first side of the ~~first plytop ply~~ 702 and thus it allows the self-mailer to be printed in a typical sheet-fed non-impact printer. Additionally, it allows the postage indicia and FIM to be printed within 1/8 of an inch of the top edge of the self-mailer, as required by the USPS.

[0076] FIG. 8 shows the ~~backside~~second side of a second ply 802 (*i.e.* ~~backside of the bottom ply~~) of the mailing form in one embodiment of the present invention. The ~~second plybottom ply~~ 802 is of the same size and constitution as the ~~first plytop ply~~ 702. As shall be seen below, the ~~second plybottom ply~~ 802 is manufactured for superimposing below, and lining up with, the ~~first plytop ply~~ 702.

[0077] FIG. 8 shows a die cut 840 running vertically along the ~~second plybottom ply~~ 802 and curving to the left to meet the left edge of the ~~second plybottom ply~~ 802. The horizontal portion of the die cut 840 is referred to as die cut 805. FIG. 8 also shows a die cut 842 running vertically along the ~~second plybottom ply~~ 802 and curving to the right to meet the right edge of the ~~second plybottom ply~~ 802. The vertical portion of the die cut is referred to as die cut 842. The horizontal portion of the die cut is referred to as die cut 841.

[0078] FIG. 8 also shows a fold line 821 running along the horizontal midsection of the ~~second plybottom ply~~ 802, starting at the die cut 840 and extending to the left edge of the ~~second plybottom ply~~ 802. Die cut 841 is collinear with fold line 821. FIG. 8 further shows a perforation 830 running along the top edge of the ~~second plybottom ply~~ 802, starting at the die cut 840 and extending to the left

EXPRESS MAIL LABEL NO. EV343427046US

edge of the ~~second-plybottom ply~~ 802. FIG. 8 further shows a perforation 831 running along the bottom edge of the ~~second-plybottom ply~~ 802, starting at the die cut 840 and extending to the left edge of the ~~second-plybottom ply~~ 802.

[0079] Die cuts 840, 841, 805 and 842 bound the area of the removable portion 803 of the ~~second-plybottom ply~~ 802. Because a die cut is a continuous cut of the material that constitutes ~~second-plybottom ply~~ 802, die cuts 840, 841, 805 and 842 effectively disconnect the removable portion 803 from the rest of the ~~second-plybottom ply~~ 802. The removable portion 803 and its functions are described in greater detail below.

[0080] When the ~~first-plytop ply~~ 702 is superimposed on top of ~~second-plybottom ply~~ 802, the perforation 830 is collinear with the perforation 730, the perforation 831 is collinear with the perforation 731, the fold line 821 is collinear with the fold line 721 and a substantial portion of the die cut 840 is collinear with the fold line 720. Furthermore, die cut 805 is collinear with die cut 741, die cut 841 is collinear with fold line 721 and die cut 842 is collinear with perforation 722.

[0081] FIG. 9 shows the ~~backside~~second side of the bottom ply (i.e. backside of the bottom ply) of the mailing form 900, or self-mailer, in one embodiment of the present invention. The mailing form 900 comprises the ~~first-plytop ply~~ 702 laid on top of the ~~second-plybottom ply~~ 802 such that the ~~front-face~~first side of the ~~second-ply of the bottom ply 202~~802 -(inner side of the bottom ply) meets the ~~back-face~~second side of the ~~first-plytop ply~~ (i.e. inner side of the top ply) 702. FIG. 9 shows the ~~back-face~~second side of the second-ply bottom ply 802 (backside of the bottom ply), as the ~~front-face~~first side of the ~~second-plybottom ply (inner side of the bottom ply)~~ 802 is not visible due to the ~~first-plytop ply~~ 702 laying on top of the ~~front-face~~first side of the ~~second-ply bottom ply (inner side of the bottom ply)~~ 802. FIG. 9 also shows the ~~back-face~~second side of the first

~~plytop ply (i.e. inner side of the top ply) 702, visible only as the second~~
~~plybottom ply 802 is peeled off.~~

[0082] As explained above, the die cuts 840, 805, 841 and 842 bound the area of the removable portion 803 of the ~~second-plybottom ply 802~~. Die cuts 840, 805, 841 and 842 effectively disconnect the removable portion 803 from the rest of the ~~second-plybottom ply 802~~. FIG. 9 shows that the removable portion 803 of the ~~second-ply bottom ply 802~~ can be removed by peeling the removable portion 803 from the self-mailer 900. The ~~front-facefirst portion~~ of the removable portion 803 of the ~~second-plybottom ply 802~~ (i.e., that face of the removable portion 803 that contacts the ~~first-plytop ply 702~~) is coated with a releasable substrate 905 such as silicon. Further, the area of the ~~back-facessecond side~~ of the ~~first-plytop ply (i.e. inner side of the top ply) 702~~ that contacts the ~~front facefirst portion~~ of the removable portion 803 is coated with an adhesive 904.

[0083] Thus, the releasable substrate 905 on the ~~front-facefirst portion~~ of the removable portion 803 of the ~~second-plybottom ply 802~~ contacts and releasably adheres to the adhesive 904 on the ~~back-facessecond side~~ of the ~~first-plytop ply (i.e. inner side of the top ply) 702~~. As the removable portion 803 of the ~~second plybottom ply 802~~ is pulled off of the ~~first-plytop ply 702~~, the releasable substrate 905 on the ~~backside~~~~second side of the top ply (i.e. inner side of the top ply)~~ of the removable portion 803 releases from the adhesive 904 on the ~~back-facessecond side~~ of the ~~first-plytop ply (i.e. inner side of the top ply) 702~~. This allows the removable portion 803 to be removed easily when pulled such that the releasable substrate 905 on the ~~front-facefirst portion~~ of the removable portion 803 releases from the adhesive 904 on the ~~back-facessecond side~~ of the ~~first-plytop ply (i.e. inner side of the top ply) 702~~.

[0084] FIG. 11 shows the ~~backside-of-the~~ removable portion 803 of the ~~second plybottom ply -802~~ in one embodiment of the present invention. FIG. 11 shows the removable portion 803 after it has been removed from the self-mailer 900.

FIG. 11 also shows the area of the ~~backside~~first side of the bottom ply (i.e. the inner side of the bottom ply) of the removable portion 803 that is covered with the releasable substrate 905.

[0085] FIG. 10 shows the ~~backside~~second side of the bottom ply (i.e. backside of the bottom ply) of the mailing form 900 after removal of the removable portion 803 of the ~~second ply~~bottom ply 802 in one embodiment of the present invention. FIG. 10 shows that after removal of the removable portion 803 of the ~~second ply~~bottom ply 802, a portion of the ~~back-face~~second side of the ~~first ply~~top ply (i.e. inner side of the top ply) 702, including the adhesive 904, is exposed. Note that portions of the ~~second ply~~bottom ply 802 have not been removed and are still present.

[0086] FIG. 10 also shows that horizontal strip 745 of the ~~first ply~~top ply 702 has been removed along with the removable portion 803 of the ~~second ply~~bottom ply 802. Horizontal strip 745 is located in the ~~first ply~~top ply 702, bounded by die cut 741 and by die cut 740. When the ~~first ply~~top ply 702 is superimposed on top of ~~second ply~~bottom ply 802, die cut 805 is collinear with die cut 741. The removable portion 803 of the ~~second ply~~bottom ply 802 is coupled with the horizontal strip 745 via adhesive or the like. When the removable portion 803 of the ~~second ply~~bottom ply 802 is removed, the horizontal strip 745, being coupled to the removable portion 803 and being detached from the rest of the ~~first ply~~top ply 702, is removed along with the removable portion 803.

[0087] FIG. 12 shows the ~~backside~~second side of the bottom ply (i.e. backside of the bottom ply) of the mailing form 900 during a first folding action in one embodiment of the present invention. FIG. 12 shows the self-mailer 900 being folded for mailing. FIG. 12 shows that the self-mailer 900 is folded along vertical fold line 720 such that the ~~back-face~~second side of the left side of self-mailer 900 meets the ~~back-face~~second side of the ~~right~~first side of self-mailer 900. Upon folding, note that the ~~right~~first side of the ~~back-face~~second side of the ~~first~~

EXPRESS MAIL LABEL NO. EV343427046US

~~plytop ply~~ 702 is lined with an adhesive 904. Thus, when the self-mailer 900 is folded along vertical fold line 720, the adhesive 904 contacts and adheres to corresponding areas in the opposing face. Namely, the adhesive 904 on the ~~right~~first side of the ~~first plytop ply~~ 702 contacts and adheres to corresponding areas in the left side of the ~~second plybottom ply~~ 802.

[0088] The result of the folding action of FIG. 12 is shown in FIG. 13. FIG. 13 shows the mailing form 900 after the first folding action in one embodiment of the present invention. FIG. 13 shows that after folding along the vertical fold line 720, the areas 710 and 711 are exposed. In one embodiment of the present invention, document information can be printed in areas 710 and 711. FIG. 13 also shows that a horizontal strip 1302 including adhesive 904 is also exposed due to the removal of the horizontal strip 745, as described with reference to FIG. 10 above.

[0089] FIG. 14 shows the mailing form 900 during a second folding action in one embodiment of the present invention. FIG. 14 shows the self-mailer 900 being further folded for mailing. FIG. 14 shows that the self-mailer 900 is folded along horizontal fold line 721 such that the area 710 of self-mailer 900 meets the area 711 of self-mailer 900. Upon folding, note that the horizontal strip 1302 is lined with an adhesive 904. Thus, when the self-mailer 900 is folded along horizontal fold line 721, the adhesive 904 contacts and adheres to corresponding areas in the opposing face. Namely, the adhesive 904 on the horizontal strip 1302 contacts and adheres to corresponding areas below the perforation 731 of the ~~first plytop ply~~ 702.

[0090] The result of the folding action of FIG. 14 is shown in FIG. 15. FIG. 15 shows the mailing form 900 after the second folding action in one embodiment of the present invention. FIG. 15 shows that after folding along the horizontal fold line 721, the area 713 of the ~~first plytop ply~~ 702 is exposed. In one embodiment of the present invention, variable information can be printed in area

EXPRESS MAIL LABEL NO. EV343427046US

713. FIG. 15 also shows that upon folding along the horizontal fold line 721, perforation 730 and 731 are collinear.

[0091] The foregoing features of the present invention are advantageous as they result in document information being firmly situated between layers of paper of the ~~first plytop ply~~ 702 and the ~~second plybottom ply~~ 802. Further, the document information is sealed along the edges by the adhesive 904. This produces an envelope that securely carries document information and is able to survive the rigors of mail processing by the USPS and other entities.

[0092] FIG. 16 shows the mailing form 900 during removal of a receipt in one embodiment of the present invention. FIG. 16 shows that upon folding along fold line 721, the perforation 722 folds onto itself, allowing a postal clerk of the United States Postal Office of the self-mailer 900 to tear the perforation 722 so as to detach the areas 714 and 715, which may contain receipt information and handed back to the sender.

[0093] After mailing the completely folded mailing form 900 of FIG. 15, the mailing form 900 can be opened by the delivering postal carrier or mail carrier by tearing along the perforation 730. Note that upon folding along the horizontal fold line 721, perforation 730 and 731 are collinear. Also note that the adhesive 904 on the horizontal strip 1302 contacts and adheres to corresponding areas below the perforation 731 of the ~~first plytop ply~~ 702. Thus, upon tearing along perforations 730 and 731 and discarding the resultant strip, the adhesive on horizontal strip 1302 is eliminated. The mailing form 900 can then be separated along the horizontal fold line 721, as shown in FIG. 16, exposing areas 710 and 711.

Third Embodiment

[0094] FIG. 17 shows another embodiment of the ~~backside~~first side of a first plytop ply 1702 of the mailing form, or self-mailer, in a third embodiment of the present invention. FIG. 17 is an alternative embodiment of the item depicted in FIG. 7. FIG. 17 shows that the first plytop ply 1702 is a rectangular sheet of paper having dimensions of 8.5x14 inches, for example.

~~[0100]~~[0095] FIG. 17 shows that the first plytop ply 1702 includes a vertical fold line 1720 running vertically along the first plytop ply 1702. FIG. 17 also shows that the first plytop ply 1702 includes a horizontal fold line 1721 running horizontally along the first plytop ply 1702. FIG. 17 further shows that the first plytop ply 1702 includes a perforation 1722 running vertically near the right edge of the first plytop ply 702. Additionally, FIG. 17 shows that the first plytop ply 1702 includes a perforation 1730 running along the top edge of the first plytop ply 1702 from the left edge of the first plytop ply 1702 to the perforation 1722 and a perforation 1731 running along the bottom edge of the first plytop ply 1702 from the left edge of the first plytop ply 1702 to the perforation 1722.

~~[0101]~~[0096] FIG. 17 further shows that the first plytop ply 1702 includes a die cut 1741 that runs along the top edge of the first plytop ply 1702 from vertical fold line 1720 to the left edge of the first plytop ply 1702. In addition, the first plytop ply 1702 includes a die cut 1740 that runs along the vertical fold line 1720 from the top of the first plytop ply 1702 to the die cut 1741. In one embodiment, the fold lines 1721 and 1720 are perforations.

~~[0102]~~[0097] The fold lines, perforations and die cuts of the first plytop ply 1702 create various areas in the ~~front-face~~first side of the first plytop ply 1702. Area 1710 is located in the upper portion of the first plytop ply 1702, bounded on the top by perforation 1730, bounded on the bottom by fold line 1721, bounded on the left by fold line 1720 and bounded on the right by perforation 1722. Area 1711 is located in the bottom portion of the first plytop ply 1702,

EXPRESS MAIL LABEL NO. EV343427046US

bounded on the bottom by perforation 1731, bounded on the left by fold line 1720, bounded on the top by fold line 1721 and bounded on the right by perforation 1722. Area 1712 is located in the bottom portion of the first-plytop ply 1702, bounded on the bottom by perforation 1731, bounded on the right by fold line 1720 and bounded on the top by fold line 1721. Area 1713 is located in the top portion of the first-plytop ply 1702, bounded on the bottom by fold line 1721, bounded on the right by fold line 1720 and bounded on the top by perforation 1730.

[0103][0098].....Area 1714 is located in the upper portion of the first-plytop ply 1702, bounded on the bottom by fold line 1721 and bounded on the left by perforation 1722. Area 1715 is located in the bottom portion of the first-plytop ply 1702, bounded on the left by perforation 1722 and bounded on the top by fold line 1721. Horizontal strip 1745 is located in the top portion of the first-plytop ply 1702, bounded on the bottom by die cut 1741 and bounded on the right by die cut 1740.

[0104][0099].....In one embodiment of the present invention, document information can be printed in areas 1710 and 1711. In another embodiment of the present invention, variable information can be printed in areas 1712 and 1713. In yet another embodiment of the present invention, receipt information can be printed in areas 1714 and 1715. In this embodiment, the receipt is typically a copy of information that is included in the document information of areas 1710 and 1711. The receipt is retained by the sender of the mailing form 3800 as a "Receipt for Certified Mailing" (e.g. United States Postal Form 3800 or equivalent) after being "round stamped" by the receiving postal clerk of the United States Postal Service of the self-mailer that was mailed.

[0105][0100].....In yet another embodiment of the present invention, postage indicia and FIM are printed in area 1712 or 1713 near fold line 1721, which is away from the edge of the sheet of the first-plytop ply 1702. Note that the

EXPRESS MAIL LABEL NO. EV343427046US

document information printed in the areas 1710 and 1711, the variable information printed in areas 1712 and 1713 and the receipt information printed in areas 1714 and 1715 can be printed in a downwards-facing or in an upwards facing orientation.

[0106][0101] FIG. 17 further shows labels 1771, 1772 and 1773 in area 1715. These labels can be used to print recipient address data, sender address data, postage, or any other information that can be printed onto a label and used in conjunction with the self-mailer or otherwise. Note that each label is generated by a closed die cut that encircles or encompasses the label.

[0107][0102] FIG. 18 shows another embodiment of the ~~backside~~second side of a ~~second-plybottom ply~~ 1802 of the mailing form in a third embodiment of the present invention. FIG. 18 is an alternative embodiment of the item depicted in FIG. 8. The ~~second-plybottom ply~~ 1802 is of the same size and constitution as the ~~first-plytop ply~~ 1702. As shall be seen below, the ~~second plybottom ply~~ 1802 is manufactured for superimposing below, and lining up with, the ~~first-plytop ply~~ 1702.

[0108][0103] FIG. 18 shows a die cut 1840 running vertically along the ~~second-plybottom ply~~ 1802 and curving to the left to meet the left edge of the ~~second-plybottom ply~~ 1802. The horizontal portion of the die cut 1840 is referred to as die cut 1815. FIG. 18 also shows a die cut 1842 running vertically along the ~~second-plybottom ply~~ 1802 and curving to the right to meet the right edge of the ~~second-plybottom ply~~ 1802. The vertical portion of the die cut is referred to as die cut 1842. The horizontal portion of the die cut is referred to as die cut 1841. FIG. 18 also shows a die cut 1805 that starts at the left edge of the ~~second-plybottom ply~~ 1802 extends out onto the self mailer and returns to the left edge of the ~~second-plybottom ply~~ 1802. A strip 1850 consists of a strip of ply that is formed from the die cuts 1805 and 1815.

[0109][0104] FIG. 18 further shows a perforation 1830 running along the top edge of the ~~second-plybottom ply~~ 1802, starting at the die cut 1840 and extending to the left edge of the ~~second-plybottom ply~~ 1802. FIG. 18 further shows a perforation 1831 running along the bottom edge of the ~~second-plybottom ply~~ 1802, starting at the die cut 1840 and extending to the left edge of the ~~second-plybottom ply~~ 1802.

[0110][0105] Die cuts 1840, 1841, 1815, 1805 and 1842 bound the area of the removable portion 1803 of the ~~second-plybottom ply~~ 1802. Because a die cut is a continuous cut of the material that constitutes ~~second-plybottom ply~~ 1802, die cuts 1840, 1841, 1815, 1805 and 1842 effectively disconnect the removable portion 1803 from the rest of the ~~second-plybottom ply~~ 1802. The removable portion 1803 and its functions are described in greater detail above.

[0111][0106] When the ~~first-plytop ply~~ 1702 is superimposed on top of ~~second-plybottom ply~~ 1802, the perforation 1830 is collinear with the perforation 1730, the perforation 1831 is collinear with the perforation 1731, the strip 1850 is collinear with the fold line 1721 and a substantial portion of the die cut 1840 is collinear with the fold line 1720. Furthermore, die cut 1805 is collinear with die cut 1741, die cut 1841 is collinear with fold line 1721 and die cut 1842 is collinear with perforation 1722.

[0112][0107] It should be noted that the difference between the item depicted in FIG. 8 and the item depicted in FIG. 18 is the presence of the strip 1850 in the mailer of FIG. 18, which is not present in the mailer of FIG. 8. When the removable portion 1803 of the ~~second-plybottom ply~~ 1802 is removed, this exposes the ~~first-plytop ply~~ 1702. The strip 1850 is integrated with the removable portion 1803 and is thus removed when the removable portion 1803 is removed. Note that strip 1850 covers the midline of the self mailer, under which fold line 1721 of FIG. 17 is located. The advantage of strip 1850 is that upon removal of the removable portion 1803, the fold line 1721 is exposed and

EXPRESS MAIL LABEL NO. EV343427046US

allows for easier folding of the self mailer. Folding is inherently easier when one piece of paper (or one ply) is folded, as opposed to two pieces of paper (or two ply).

[0113][0108] Although specific embodiments of the invention have been disclosed, those having ordinary skill in the art will understand that changes can be made to the specific embodiments without departing from the spirit and scope of the invention. The scope of the invention is not to be restricted, therefore, to the specific embodiments. Furthermore, it is intended that the appended claims cover any and all such applications, modifications, and embodiments within the scope of the present invention.

[0114][0109] What is claimed is:

EXPRESS MAIL LABEL NO. EV343427046US

MULTI-LABEL MAILING FORM INCLUDING CERTIFIED SELF-MAILER

ABSTRACT OF THE DISCLOSURE

A mailing form for facilitating the mailing of a document is disclosed. The mailing form includes a bottom ply of the mailing form and an interspersed ~~between the front face of the~~ first side of the bottom ply (i.e. inner side of the bottom ply) and the ~~backside~~second side of the top ply ~~-(i.e. inner side of top ply)~~. The mailing form further includes a top ply of the mailing form and a removable portion of the top ply extending over the first side of the top ply. The mailing form further includes a vertical fold line for folding the mailing form after the top ply has been removed, and a horizontal strip of the ~~front face~~first side of the bottom ply ~~located on the first side of the bottom ply~~, the horizontal strip including adhesive that is exposed after the mailing form is folded. The mailing form further includes a horizontal fold line for folding the mailing form that has been folded along the vertical fold line.

542-P0035_v8.doc